



Product Specification Sheet

TS/6-61BP250

PreMoist Swab - Blue Polystyrene shaft/Viscose 45mm breakpoint Swab, pre-moistened in TSC Neutralising Buffer sealed in tube

Product Code	TS/6-61BP250
Description	PreMoist Swab - Blue Polystyrene shaft/Viscose 45mm breakpoint Swab, pre-moistened in TSC Neutralising Buffer sealed in tube
Intended Use	Sampling of surfaces for environmental and hygiene monitoring and cleaning validation. Suitable for critical food areas.
Components	Polypropylene Tube, Blue HDPE Standard Cap, Blue Polystyrene/Viscose Swab (breakpoint at 45 mm), Label, Hot melt glue.
Contents	De-ionised Water, Tween 80, Lecithin, Sodium Thiosulphate, Sodium Thioglycollate, Sodium sulfite, Buffers to maintain pH - 7.2 ± 0.2 .
Method of Sterilisation	Sterilised by gamma irradiation at dosage of 25-53.4kGy
Shelf Life	24 months from date of manufacture
Storage Conditions	4-25°C. Store in dry and ventilated area; protect from light, heat and moisture in tightly closed original packaging
Precautions and Limitations	Analyse as soon as possible due to the small volume, so to minimise sample dryout and organism loss. Refrigeration will stabilise recovery of some organisms. Not suitable for most fastidious organism unless analysed immediately. Due to product characteristics a small precipitate may be observed which does not affect performance.
Pack Size	250 in a box
Other	Quality control testing details on final product: i) Validation of irradiation sterility ii) Product appearance.

This specification (and formulation where applicable) are intended for guidance only and may be adjusted to meet product defined criteria.

You should always refer to a professional with experience in your intended application if in any doubt.

FMCG Industry Solutions Pty Ltd

ABN 22 135 446 007

📍 Factory 11A, 1 - 3 Endeavour Rd, Caringbah NSW 2229

🌐 www.fmcgis.com.au

✉ sales@fmcgis.com.au

☎ 1300 628 104 or 02 9540 2288

